



SS Stainless Steel

Type

- DK** With triangular spindle
- VK7** With square spindle
- VK8** With square spindle
- SCH** With slot
- VDE** With double bit

Metric table

Dimensions in: millimeters - inches

Latch arm distance A													
6	10	14	18	20	22	24	26	28	30	34	38	40	50
0.24	0.39	0.55	0.71	0.79	0.87	0.94	1.02	1.10	1.18	1.34	1.50	1.57	1.97

Specification

- Cam latch housing
Stainless steel AISI 303
- Latch arm
Stainless steel AISI 304
- Other parts
Stainless steel AISI 304
- Protection class IP 65
- *IP Protection Classes* → page 2130
- *Stainless Steel Characteristics* → page 2143
- **RoHS compliant**

Accessory

- Socket keys GN 119.2 → page 1310
- Protective caps GN 120
→ www.jwwinco.com
- Opening handles GN 120.1
→ www.jwwinco.com
- Protective guide plates GN 120.2
→ www.jwwinco.com
- Internal cabinet handles GN 120.3 → page XYZ
- Sheet metal punches GN 123 → page XYZ

On request

- Other operations

Information

GN 115 cam latches lock by a turning operation limited to 90° which moves the latch arm in the locked position behind the door frame. The bevels of the latch arm ease the closing of the door.

Thanks to the stainless steel materials used, the latches are optimally suited for use in corrosive environments.

Latch arms are available with different bend angles to cover a latch arm distance A from 6 to 50 mm.

Product comes supplied with a loosely enclosed latch arm.

see also...

- *Construction and Assembly Instructions* → page 1261
- *List of Cam Latch / Cam Lock Types* → page 1256
- *Cam Latches GN 115 (Zinc Die-Cast, with Operation with Socket Key)* → page 1260
- *Cam Latches GN 515 (with Extended Housing)* → starting from page XYZ
- *Cam Latches GN 115.6 (Stainless Steel, Small Type)* → page XYZ

How to order

GN 115-DK-18-NI

- 1 Type
- 2 Latch arm distance A
- 3 Material

3.1
3.2
3.3
3.4
3.5
3.6
3.7
3.8
3.9
3.10