



- 3 Identification no.**
- 2** With stainless steel socket cap screw DIN 912

Metric table

Dimensions in: millimeters - inches

1 d ₁ Bore for clamping Ø	2 d ₂ Bore for sensor	b Swivel width	d ₃	k	l ₁	l ₂	m	t	z Screw location for screw size	Accessory Recommended lever GN 911 for z l ₃	
B 20	B 18 B 30	40 1.57	50 1.97	40 1.57	95 3.74	40 1.57	43 1.69	10 0.39	M8-25	-	-
B 25	B 18 B 30	40 1.57	50 1.97	40 1.57	95 3.74	40 1.57	43 1.69	10 0.39	M8-25	63 2.48	78 3.07
B 30	B 18 B 30	40 1.57	50 1.97	40 1.57	95 3.74	40 1.57	43 1.69	10 0.39	M8-25	63 2.48	78 3.07

Specification

- Body
Aluminum
Powder coated
Black, RAL 9005, textured finish **● SW**
- Socket cap screws DIN 912
Stainless steel AISI 304
- Hex nuts DIN 985
Stainless steel AISI 304
Self-locking via polyamide ring
- *Stainless Steel Characteristics* → page QVX
- **RoHS compliant**

Information

The clamping bore of sensor holders GN 278.4 is mechanically machined and designed for construction tubes GN 990 or DIN 2391, DIN 2395 and DIN 2462.

At the screw location **z**, the socket cap screw reduces the bore cross-section for clamping.

For clamping without tools, the socket cap screw can be replaced by an adjustable lever GN 911 listed in the table as accessory.

see also...

- *Construction Tubes GN 990* → page QVX
- *Round Rods / Tubes GN 480.1* → page QVX
- *Attachment Mounting Clamps GN 478* → page QVX

Accessory

- Adjustable levers GN 911 → page QVX

<p>How to order</p> <p>GN 278.4-B30-B30-2-SW</p>	1 Bore d ₁
	2 Bore d ₂
	3 Identification no.
	4 Finish