



**Inch table**

Dimensions in: inches - millimeters

<sup>1</sup> d <sub>1</sub>	<sup>2</sup> d <sub>2</sub>	<sup>3</sup> Length l			b	h
0.98 24.9	10 x 32	0.50 12.7	0.75 19.1	-	0.43 10.9	0.51 13.0
1.26 32.0	1/4 x 20	0.50 12.7	0.75 19.1	1.00 25.4	0.51 13.0	0.59 15.0
1.57 39.9	5/16 x 18	0.75 19.1	1.00 25.4	-	0.61 15.5	0.67 17.0

**Metric table**

Dimensions in: millimeters - inches

<sup>1</sup> d <sub>1</sub>	<sup>2</sup> d <sub>2</sub>	<sup>3</sup> Length l			b	h
20 0.79	M 4	6 0.24	10 0.39	-	9.5 0.37	11 0.43
25 0.98	M 5	10 0.39	16 0.63	-	11 0.43	13 0.51
32 1.26	M 5	10 0.39	16 0.63	20 0.79	-	13 0.51
32 1.26	M 6	10 0.39	16 0.63	20 0.79	25 0.98	30 1.18
32 1.26	M 6	10 0.39	16 0.63	20 0.79	25 0.98	30 1.18
32 1.26	M 8	16 0.63	20 0.79	25 0.98	40 1.57	45 1.77
40 1.57	M 5	10 0.39	16 0.63	20 0.79	-	-
40 1.57	M 6	16 0.63	20 0.79	25 0.98	30 1.18	40 1.57
40 1.57	M 8	16 0.63	25 0.98	40 1.57	-	-
40 1.57	M 10	20 0.79	30 1.18	40 1.57	-	-
48 1.89	M 8	16 0.63	25 0.98	-	-	-
56 2.20	M 10	20 0.79	30 1.18	-	-	-

**Specification**

- Wing body  
Plastic  
Technopolymer (Polyamide PA)  
- Glass fiber reinforced  
- Temperature resistant up to 266 °F (130 °C)  
- Black, matte finish
- Threaded stud  
Steel, zinc plated, blue passivated finish
- *Plastic Characteristics* → page 2135
- RoHS compliant

**Information**

Due to their low height EN 531 wing screws offer a comfortable grip for quick two finger clamping applications.

Resistant to solvents, oils, grease and other chemical agents.

see also...

- *Wing Screws EN 531.1 (with Protruding Hub)* → page 669
- *Wing Screws EN 633* → page 663

How to order <b>EN 531-1.26-1/4X20-1.00</b>	<sup>1</sup>	Handle diameter d <sub>1</sub>
	<sup>2</sup>	Thread d <sub>2</sub>
	<sup>3</sup>	Length l