



SS Stainless Steel

Metric table

Dimensions in: millimeters - inches

¹ d ₁	² d ₂	³ l ₁				⁴ d ₃	d ₄	d ₅ +0.05	h ₁	h ₂	l ₂	l ₃	l ₄
32 1.26	M 6	25 0.98	35 1.38	45 1.77	-	15 0.59	14 0.55	4.5 0.18	20 0.79	10 0.39	5.1 0.20	3.6 0.14	7.6 0.30
40 1.57	M 8	30 1.18	40 1.57	50 1.97	60 2.36	18 0.71	18 0.71	6.1 0.24	25 0.98	13 0.51	6.2 0.24	4.2 0.17	9.2 0.36
40 1.57	M 8	30 1.18	40 1.57	50 1.97	60 2.36	21 0.83	18 0.71	6.1 0.24	25 0.98	13 0.51	6.2 0.24	5 0.20	10 0.39
40 1.57	M 8	30 1.18	40 1.57	50 1.97	60 2.36	25 0.98	18 0.71	6.1 0.24	25 0.98	13 0.51	6.2 0.24	5.5 0.22	10.5 0.41
40 1.57	M 8	30 1.18	40 1.57	50 1.97	60 2.36	32 1.26	18 0.71	6.1 0.24	25 0.98	13 0.51	6.2 0.24	6 0.24	11 0.43
40 1.57	M 8	30 1.18	40 1.57	50 1.97	60 2.36	40 1.57	18 0.71	6.1 0.24	25 0.98	13 0.51	6.2 0.24	8 0.31	13 0.51
50 1.97	M 10	35 1.38	45 1.77	55 2.17	65 2.56	21 0.83	22 0.87	7.8 0.31	32 1.26	17 0.67	7.3 0.29	4.3 0.17	10 0.39
50 1.97	M 10	35 1.38	45 1.77	55 2.17	65 2.56	25 0.98	22 0.87	7.8 0.31	32 1.26	17 0.67	7.3 0.29	4.6 0.18	10.5 0.41
50 1.97	M 10	35 1.38	45 1.77	55 2.17	65 2.56	32 1.26	22 0.87	7.8 0.31	32 1.26	17 0.67	7.3 0.29	5 0.20	11 0.43
50 1.97	M 10	35 1.38	45 1.77	55 2.17	65 2.56	40 1.57	22 0.87	7.8 0.31	32 1.26	17 0.67	7.3 0.29	7 0.28	13 0.51
63 2.48	M 12	40 1.57	60 2.36	80 3.15	-	25 0.98	26 1.02	9.4 0.37	40 1.57	21 0.83	8.3 0.33	3.6 0.14	10.5 0.41
63 2.48	M 12	40 1.57	60 2.36	80 3.15	-	32 1.26	26 1.02	9.4 0.37	40 1.57	21 0.83	8.3 0.33	4.2 0.17	11 0.43
63 2.48	M 12	40 1.57	60 2.36	80 3.15	-	40 1.57	26 1.02	9.4 0.37	40 1.57	21 0.83	8.3 0.33	6.2 0.24	13 0.51
63 2.48	M 12	40 1.57	60 2.36	80 3.15	-	50 1.97	26 1.02	9.4 0.37	40 1.57	21 0.83	8.3 0.33	8.7 0.34	15.5 0.61

Specification

- Star knob DIN 6336
Plastic
Technopolymer (Polyamide PA)
Black, matte finish
- Threaded stud
Stainless steel AISI 304 Cu
- Thrust pad GN 631
Plastic
Technopolymer (Polyacetal POM)
- Temperature resistant up to 176 °F (80 °C)
- Black, matte finish
- *Plastic Characteristics* → page 2135
- *Stainless Steel Characteristics* → page 2143
- RoHS compliant

Information

GN 6336.11 and GN 6336.12 star knobs with stainless steel threaded stud have a ball end whose diameter is smaller than the core diameter of the thread.

These components are an excellent choice for corrosion-free applications.

The swivel thrust pad is easily clipped on and taken off. Thrust pads are supplied unmounted.

see also...

- *Hollow Knurled Knobs GN 421.12 (with Swivel Thrust Pad)* → www.jwwinco.com
- *Star Knobs GN 6336.11 / GN 6336.12 with Loss Protection GN 111.7* → page 2046

How to order (With ball end)	¹ Handle diameter d ₁
²	² Thread d ₂
³	³ Length l ₁
GN 6336.11-40-M8-50	

How to order (With swivel thrust pad)	¹ Handle diameter d ₁
²	² Thread d ₂
³	³ Length l ₁
⁴	⁴ Thrust pad diameter d ₃
GN 6336.12-50-M10-45-25	