



Metric table



Dimensions in: millimeters - inches

l_1	s					d	l_2	l_3
30 <i>1.18</i>	0.1 <i>0.004</i>	0.2 <i>0.08</i>	0.3 <i>0.012</i>	0.5 <i>0.020</i>	1 <i>0.039</i>	9.2 <i>0.36</i>	13 <i>0.51</i>	17 <i>0.67</i>
40 <i>1.57</i>	0.1 <i>0.004</i>	0.2 <i>0.08</i>	0.3 <i>0.012</i>	0.5 <i>0.020</i>	1 <i>0.039</i>	11.2 <i>0.44</i>	17 <i>0.67</i>	23 <i>0.91</i>
50 <i>1.97</i>	0.1 <i>0.004</i>	0.2 <i>0.08</i>	0.3 <i>0.012</i>	0.5 <i>0.020</i>	1 <i>0.039</i>	13.2 <i>0.52</i>	20 <i>0.79</i>	30 <i>1.18</i>
60 <i>2.36</i>	0.1 <i>0.004</i>	0.2 <i>0.08</i>	0.3 <i>0.012</i>	0.5 <i>0.020</i>	1 <i>0.039</i>	13.2 <i>0.52</i>	20 <i>0.79</i>	40 <i>1.57</i>

Specification

- Steel
- RoHS compliant

Information

GN 871 shim kits are used to correct any discrepancy in the alignment of the jaw blocks. This provides a simple way to optimize the clamping position of the GN 872 jaw blocks, i. e. also the optimal clamping force. The shims kits are only available as a complete set of five with different thicknesses for each size.

<p>How to order</p> <p>GN 871-40</p>	<p>1 Length l_1</p>
---	----------------------------------